

CH-5036 Oberentfelden

PI-06404

Rev. 1

Product info

Decont area

Page 1 / 2

Decontamination shower

Portable shower unit allows an effective decontamination of protective suits. The decontamination shower is suitable as a permanent installation as well as for the operation of an emergency centre or in the intervention case for rescue services.

- portable case for storage and transport and serves as a base plate at the same time
- quick and easy installation
- hoses made of chemical and heat resistant material
- 12 spray nozzles for efficient decontamination, produce an instant pollutant dilution in the ratio 2000: 1
- operational pressure: 3.0 - 5.5 bar max. static pressure: 10 bar
- water flow rate: 800 1100 l/min.
- connection: Storz-C quick coupling (standard) or according to customer request.



weight: 23 kg



Item no	Description
115579	Decontamination shower

Decontamination shower with housing, inflatable

Mobile, inflatable shower unit for effective personal decontamination. The decontamination shower is suitable as a permanent installation as well as for the operation of an emergency center or in the intervention case for rescue services.

- with internal shower cabin and water collecting basin
- with integrated water pipe, 5 spray nozzles and hand shower
- with gloves, integrated in sidewall
- inflating with blower or compressed air cylinder assembly time blower: 150 sec / 0.15 bar assembly time compressed air bottle : 70 sec / 0.30 bar bottle requirement: 1 Bottle 6 I / 300 bar number of air chambers: 1
- dimensions: external dimensions: 2.50 x 2.50 x 2.70 m
 Pack weight: 1.10 x 0.80 x 0.60 m
 Usable area: 2.5 m²
- connection: Storz-C quick coupling (standard)
- weight: 39 kg
- included in delivery:
 - Accessory material (hammer, pegs, storm ropes, etc.)
 - Packing bag for tent and accessories
- optionally available:
 - Connection set for compressed air filling

Item no	Description
115580	Decontamination shower with housing, inflatable, complete
115633	Connection set for compressed air filling, consisting of: Pressure reducer 300 bar, compressed air hose 1 m, quick release coupling

